



**ANY JOB.  
ANY SIZE.  
ANY PLACE.**

55 Years of American Ingenuity

# 2300



The **2300** is specifically designed for the busy contractor who is increasing his business. Capable of blowing all brands of cellulose and fiberglass to the manufacturer's specifications.

- Adaptable fold down loading door
- Removable all steel airlock allows quick access for maintenance
- User friendly electric dashboard
- Clear acrylic safety guard allows for easy inspection
- Durable powder coat finish
- Large hopper capacity for less reloading time
- Built in tool holder
- Optional 4 blower upgrade

## MATERIAL PRODUCTION RATE

### MATERIAL

<b>CELLULOSE</b>	<b>3000 (1360) *</b> <b>100 Bags per hr.*</b>
<b>FIBERGLASS</b>	<b>1000 (454) *</b> <b>33 Bags per hr.*</b>

\* lbs/hr (kg/hr) rating with 150 ft. (45.8 m.) of 3" (7.6 cm.) hose at 16 ft. (4.8 m.) elevation.

### NOTE:

Manufacturer's product brand, density and variable blowing conditions will affect production rate.

Backed by a manufacturer's  
**2-YEAR WARRANTY - Made in the U.S.A.**



# KRENDL

The Innovator in Insulation Equipment™

# 2300

Scan to learn more about Krendl Machine

### • POWER REQUIREMENT •

Double input, 30/20 amps each/120 volt/60hz

Single input, 30 amp 240volt/60hz

International -Double input, 230volt/50hz

CE/CSA/CUL/UL

\* Optional 4 blower -Single Input , 50amp 240v/60hz

### • HOPPER CAPACITY •

40 cu. ft. (1.13 m<sup>3</sup>)

Loading made easy with built in adaptable tray

### • WEIGHT/DIMENSIONS •

846 lbs / 32"W x 62"D x 68"H

384 kg./ 81cm x 157cm x 173cm

### • BLOWER/SIZE •

14amp/2-stage (120volt)

Double Blower System yields

140 CFM @ 3 1/2 PSI per blower

### • AIRLOCK •

#### Slideout Airlock System

16" x 12" diameter

(40.6cm. x 30.5cm. diameter)

3" (7.6cm.) Outlet

### • 2 HP Direct Drive Motor/Reducer •

w/overload protection



### Electric Dashboard

- LED start & stop buttons • Digital hourmeter
- Digital voltmeter • Dual variable blower speed controls
- Recessed power supply



### Dual Agitators

Designed for Constant Material Flow



### Clear Acrylic Safety Guard

Allows for Inspection