

FIBER FORCE



Insulation Blowing Machine



The FiberForce represents the best Do-It-Yourself insulation blowing technology available, refined and enhanced with your ideas and suggestions. What's more, the FiberForce utilizes proven airlock technology for simplicity and minimal downtime. The result is the best light-weight Do-It-Yourself machine on the market, tailored to meet your demanding requirements.



The Finest Do-It-Yourself portable insulation machine on the market, just see why!

The unique design and high performance of the FiberForce offers the following benefits to the small contractor and Do-It-Yourselfer:

FEATURES INCLUDE:

- **Built-in GFCI protection**
- **Hinged loading tray**
- **Light & portable**
- **Removable hopper**
- **Lift handles**
- **Twist lock power cord**
- **High production rate**
- **Wireless remote**
- **Best in-class arc length**
- **Durable all plastic construction**
- **Dual agitation system**
- **Polyurethane seals**
- **Easy clean filter**
- **Hour meter**
- **Slide gate (optional)**



COMES STANDARD WITH

PRODUCTION



- Quick disconnect hose connector
 - (1) Male attachment
 - (2) Female attachment
- (3) 2 1/2" Stainless steel hose clamp
- (1) 50' 12/3 Twist lock power cord
- (2) 50' x 2 1/2" Blowing hose
- (1) Wireless remote



Cellulose Production
1,050 lbs per hour
476 kg per hour



Fiberglass Production
428 lbs per hour
194 kg per hour

Specifications



Height	48.625" / 124.5 cm
Width	29.25" / 74.3 cm
Length (base)	28.125" / 71.4 cm
Weight (machine only)	150 lbs / 68.2 kg
Weight (shipping)	222 lbs / 100.70 kg
Production	1,050 lbs/hr - Cellulose 476 kg/hr - Cellulose 428 lbs/hr - Fiberglass 194 kg/hr - Fiberglass
Hose w/wireless remote control	2-1/2" x 50' 63.5 mm x 15.2 meter
Wireless remote (range)	250' / 76.2 meters
Gear motor	.38 HP @ 82 RPM
Gear motor torque	296 in/lb / 341 cm/kg
Blower (single stage)	145 cfm / 2.8 psi 4.08 m ³ / 0.193 bar
Electrical	115VAC @ 14 amps 1610 Watts
Power cord, type SJO (twist lock)	14/3 x 50' / 15.2 meter
Warranty	12 month (Limited Warranty)

* 230 VAC / 50 Hz available upon request

Machine Features



The Fiberforce offers complete portability with its 2- piece design and built in handles & wheels, providing the ability to transport in almost any type vehicle and access any jobsite.



Convenient hose quick disconnects come standard with every FiberForce unit for easy attachment /removal of hose in seconds.



Access panels on either side of the machine makes performing maintenance a snap.



Conveniently located start and stop buttons allows for less confusion when blowing insulation.

Options



Slide Gate

Accessories



Hose Bag



Generators



Hose Swivels
2"-6" Available

Distributed By

The Intec Pledge

Provide the finest equipment in the industry with the highest standards while continuing to strive for 100% satisfaction.

Manufactured By



1-800-666-1611

P.O. Box 579
3771 Monarch Street
Frederick, CO 80530 USA

Local: 303-833-6644
Fax: 303-833-6650
www.inteccorp.com