

HC19689 Seaming Tape

PRODUCT DATA SHEET



CONSTRUCTION

Substrate: Polymeric Film

Adhesive: Butyl Rubber

Liner: 50-lb DK Liner

FEATURES

High tack adhesive

Conformable and flexible

TYPICAL PROPERTIES

Test	Typical Values (English)	Typical Values (metric)	Test Method
Total Thickness without Liner	4.7-mil	0.119-mm	PSTC-133
Coating Thickness	2.7-mil	0.067-mm	PSTC-133
Peel Adhesion to Stainless Steel	150-oz/in	16.42-N/cm	PSTC-101
Elongation	290%	290%	PSTC-131

APPLICATION

Application surface must be clean, dry and free of contaminants.

SHELF LIFE & STORAGE

Under ideal storage conditions of 60°F to 80°F and low humidity, shelf life is one year from date of purchase.

STANDARD CONFIGURATIONS & PACKAGING (CUSTOM CONFIGURATIONS & PACKAGING AVAILABLE UPON REQUEST)

Roll Width	Roll Length	Rolls/Carton	Cartons/Pallet
3-in	165-ft	16	27

Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance. Values represent nominal and average values; individual roll values may vary from average values indicated on the data sheet. User is responsible for determining suitability and fitness for use. Revision 8.15.2014 16:03.