

Section 1 - Product and Company Identification

Hazard Label WARNING label

Company Information

Johns Manville
Insulation Systems
P.O. Box 5108
Denver, CO 80127 USA

Telephone: 303-978-2000 8:00AM-5:00PM M-F
Internet Address: <http://www.jm.com>
Emergency: 800-424-9300 (Chemtrec, In English)

Trade Names: Insul-SHIELD® Coated Black Roll, FSK-25 and PSK; Insul-SHIELD® Faced Board

Use: Product is designed for insulating exterior structural wall cavities or curtain walls.

Section 2 - Hazards Identification

Emergency Overview

Inhalation of excessive amounts of dust from the product may cause temporary upper respiratory irritation and/or congestion--remove individual to fresh air.

Inhalation

Irritation of the upper respiratory tract (scratchy throat), coughing, and congestion may occur in extreme exposures.

Skin

Temporary irritation (itching) or redness may occur.

Ingestion

This product is not intended to be ingested (eaten). If ingested, it may cause temporary irritation to the gastrointestinal (digestive) tract.

Eyes

Temporary irritation (itching) or redness may occur.

Ears

Temporary irritation (itching) or redness may occur.

Primary Routes of Entry (Exposure)

Eyes, skin, inhalation (breathing dust and fibers) and ingestion.

Target Organs

Nose (nasal passages), throat, lungs, skin, eyes

Medical Conditions Aggravated by Exposure

Pre-existing chronic respiratory, skin, or eye diseases or conditions.

Section 3 - Composition/Information on Ingredients

CAS #	Component	Percent
Not Available	Fiber glass wool	85-98
25104-55-6	Urea extended phenol-formaldehyde binder (cured)	5-15
Not Available	FSK and PSK facings	0-6.7
1333-86-4	Carbon black (encapsulated)	<1
1309-64-4	Antimony trioxide (may be in facing or adhesive)	>0.1
50-00-0	Formaldehyde	<0.1

Component Information

Antimony trioxide (fire retardant) may be present in the facings and/or adhesives. Occupational exposure to airborne antimony trioxide is not expected to occur due to product form(s) and intended use(s). Exposure limit is given for reference only.

Formaldehyde may be released by partial hydrolysis of the urea formaldehyde polymer.

General Product Description

Black rolls of inorganic glass fibers bonded with a thermosetting binder.

White boards of inorganic glass fibers bonded with a thermosetting binder.

Section 4 - First Aid Measures

First Aid: Inhalation

If dust is inhaled in excess of exposure limits referenced in section 8 of this safety data sheet, remove individual to fresh air. Drink water to clear throat, and blow nose to remove dust. A saline spray in the nose may help clear any fibers.

First Aid: Skin

Wash gently with soap and water to remove dust and fibers. Alternatively, fibers can be removed from the skin by use of ordinary masking or wrapping tape. Should irritation persist, seek medical attention.

First Aid: Ingestion

Rinse mouth with water to remove dust and fibers and drink plenty of water to help reduce irritation. If irritation persists, seek medical attention.

First Aid: Eyes

Do not rub or scratch eyes. Dust particles may cause the eye to be scratched. Flush eyes with large amounts of water until irritation subsides. If irritation persists, seek medical attention.

First Aid: Ears

Wash exposed skin with soap and water. If irritation develops in the inner ear, seek medical attention.

First Aid: Notes to Physician

Dust from the product may cause mechanical irritation of the eyes, skin, and upper respiratory tract. Treat symptomatically.

Section 5 - Fire Fighting Measures

Flash Point: Not applicable

Upper Flammable Limit (UFL): Not applicable

Auto Ignition: Not determined

Rate of Burning: Not determined

General Fire Hazards

There is no potential for spontaneous fire or explosion. Inorganic glass fibers are naturally non-combustible and non-flammable.

Extinguishing Media

Carbon dioxide (CO₂), water, water fog, dry chemical.

Fire Fighting Equipment/Instructions

No special procedures are expected to be necessary for this product. Normal fire fighting procedures should be followed to avoid inhalation of smoke and gases.

Section 6 - Accidental Release Measures

Clean-Up Procedures

Pick up large pieces. Vacuum dusts. If sweeping is necessary, use a dust suppressant such as water. Do not dry sweep dust accumulation. These procedures will help to minimize potential exposures.

Section 7 - Handling and Storage

Handling Procedures

Use protective equipment as described in Section 8 of this safety data sheet when handling uncontained material. Handle in accordance with good industrial hygiene and safety practices.

Storage Procedures

Warehouse storage should be in accordance with package directions, if any. Material should be kept clean, dry, and in original packaging.

Section 8 - Exposure Controls / Personal Protection

The Occupational Safety and Health Administration (OSHA) has not adopted specific occupational exposure standards for fiber glass. Fiber glass is treated as a nuisance dust and is regulated by OSHA as a particulate not otherwise regulated (total dust) shown in CFR 1910.1000 Table Z-3.

Respirable fraction 5 mg/m³

Total dust 15 mg/m³

JM has adopted the fiber glass industry voluntary Product Stewardship Program (PSP), formerly the NAIMA-OSHA Health and Safety Partnership Program (HSPP). Under the PSP, JM recommends that exposures be limited to the voluntary concentration of 1 f/cc TWA for fibers longer than 5 microns with a diameter less than 3 microns. This will help minimize potential irritation effects. The PSP also includes the PPE recommendations described below.

Carbon black (encapsulated) (1333-86-4)

ACGIH: 3.5 mg/m³ TWA

OSHA: 3.5 mg/m³ TWA

Antimony trioxide (may be in facing or adhesive) (1309-64-4)ACGIH: 0.5 mg/m³ TWA (related to Antimony)OSHA: 0.5 mg/m³ TWA (related to Antimony)**Formaldehyde (50-00-0)**

ACGIH: 0.3 ppm Ceiling

OSHA: 0.5 ppm Action Level; 0.75 ppm TWA; 2 ppm STEL (Irritant and potential cancer hazard - see 29 CFR 1910.1048)

PERSONAL PROTECTIVE EQUIPMENT**Personal Protective Equipment: Eyes/Face**

Safety glasses with side shields are recommended to keep dust out of the eyes.

Personal Protective Equipment: Ears

Use ear protection (earplugs, hood, or earmuffs) to prevent airborne dust or fibers from entering the ear, if necessary.

Personal Protective Equipment: Skin

Leather or cotton gloves should be worn to protect against mechanical abrasion. See also Personal Protective Equipment: General, below.

Personal Protective Equipment: Respiratory

A NIOSH-approved respirator should be used if ventilation is unavailable, or is inadequate for keeping levels below the applicable exposure limits referenced in Section 8 of this SDS.

Ventilation

In fixed manufacturing settings, local exhaust ventilation should be provided at areas of cutting, milling or other processing to remove airborne dust.

Personal Protective Equipment: General

Wear a cap, a loose-fitting, long-sleeved shirt and long pants to protect skin from irritation. Exposed skin areas should be washed with soap and water after handling or working with fiber glass. Clothing should be washed separately from other clothes, and the washer should be rinsed thoroughly (run empty for a complete wash cycle). This will reduce the chances of fiber glass being transferred to other clothing.

Section 9 - Physical & Chemical Properties

Appearance:	Black rolls	Odor:	No significant odor
Physical State:	Solid	pH:	Not applicable
Vapor Pressure:	Not applicable	Vapor Density:	Not applicable
Boiling Point:	Not applicable	Melting Point:	>704°C/1300°F
Solubility (H₂O):	Nil	Specific Gravity:	Variable
Freezing Point:	Not applicable	Evaporation Rate:	Not applicable
Percent Volatile:	0	VOC:	Not determined

Section 10 - Stability & Reactivity Information**Stability**

These products are not reactive.

Hazardous Decomposition

May form carbon dioxide and carbon monoxide.

Hazardous Polymerization

Will not occur.

Section 11 - Toxicological Information**Acute Toxicity****A: General Product Information**

Dust from this product is a mechanical irritant, which means that it may cause temporary irritation or scratchiness of the throat, and/or itching of the eyes and skin.

Exposure to formaldehyde may cause eye and upper respiratory irritation, and possible respiratory or skin sensitization (allergy). If sensitization occurs, subsequent exposures to formaldehyde may worsen asthma or other respiratory problems, and cause allergic-type reactions.

B: Component Analysis - LD50/LC50

Urea extended phenol-formaldehyde binder (cured) (25104-55-6)

Oral LD50 Rat: 7 g/kg

Carbon black (encapsulated) (1333-86-4)

Oral LD50 Rat: >15400 mg/kg; Dermal LD50 Rabbit:>3 g/kg

Antimony trioxide (may be in facing or adhesive) (1309-64-4)

Oral LD50 Rat: >34600 mg/kg

Formaldehyde (50-00-0)

Inhalation LC50 Rat: 0.578 mg/L/4H; Oral LD50 Rat:500 mg/kg

Carcinogenicity

A: General Product Information

Exposure to formaldehyde has been associated with the development of nasopharyngeal cancer in laboratory animals and humans. Formaldehyde has been classified as a known human carcinogen, Group 1, by the International Agency for Research on Cancer (IARC). The US National Toxicology Program (NTP) considers formaldehyde as known to be a human carcinogen. OSHA specifically regulates formaldehyde under 29 CFR 1910.1048.

B: Component Carcinogenicity

Fiber glass wool (Not Available)

ACGIH: A3 - Confirmed animal carcinogen with unknown relevance to humans

NTP: Reasonably Anticipated To Be A Human Carcinogen (respirable size)

IARC: Group 3 - Not Classifiable (IARC Monograph 81 [2002] (listed under Man-made mineral fibres), Monograph 43 [1988])

Carbon black (encapsulated) (1333-86-4)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

IARC: Group 2B - Possibly Carcinogenic to Humans (IARC Monograph 93 posted, Monograph 65 [1996])

Antimony trioxide (may be in facing or adhesive) (1309-64-4)

ACGIH: A2 - Suspected Human Carcinogen (production)

IARC: Group 2B - Possibly Carcinogenic to Humans (IARC Monograph 47 [1989])

Formaldehyde (50-00-0)

ACGIH: A2 - Suspected Human Carcinogen

OSHA: 0.5 ppm Action Level; 0.75 ppm TWA; 2 ppm STEL (Irritant and potential cancer hazard - see 29 CFR 1910.1048)

NTP: Known to be a human carcinogen

IARC: Group 1 - Known Human Carcinogen

Chronic Toxicity

The U.S. Department of Health and Human Services, National Toxicology Program (NTP 1998, 2000, 2002) classified glass wool (respirable size) as reasonably anticipated to be a human carcinogen, based on sufficient evidence of carcinogenicity in animals. This assessment was originally prepared in 1993-1994 for the 7th Report on Carcinogens (NTP 1994), but has not been updated since then in the 8th, 9th, or 10th Reports on Carcinogens (NTP 1998, 2000, 2002).

Section 12 - Ecological Information

Ecotoxicity

A: General Product Information

No data available for this product.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Carbon black (encapsulated) (1333-86-4)

24 Hr EC50 Daphnia magna: >5600 mg/L

Antimony trioxide (may be in facing or adhesive) (1309-64-4)

96 Hr LC50 Pimephales promelas: 833.0 mg/L; 96 Hr LC50 Lepomis macrochirus: 530 mg/L; 96 Hr LC50 Brachydanio rerio: >1000 mg/L [static]
 72 Hr EC50 Selenastrum capricornutum: 67 mg/L
 7 Hr EC50 Pseudomonas putida: >3.5 mg/L
 48 Hr EC50 Daphnia magna: >1000 mg/L

Formaldehyde (50-00-0)

96 Hr LC50 Pimephales promelas: 24.1 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 0.10 mg/L [flow-through]; 96 Hr LC50 Brachydanio rerio: 41 mg/L [static]
 5 min EC50 Photobacterium phosphoreum: 9.0 mg/L; 15 min EC50 Photobacterium phosphoreum: 7.26 mg/L; 25 min EC50 Photobacterium phosphoreum: 6.81 mg/L; 30 min EC50 Photobacterium phosphoreum: 16.5 mg/L; 1 Hr EC50 Vibrio harveyi: 1.2 mg/L; 5 Hr EC50 Vibrio harveyi: 3.7 mg/L; 72 Hr EC50 Colpoda aspera: 5.39 mg/L
 96 Hr EC50 water flea: 20 mg/L; 48 Hr EC50 Daphnia magna: 2 mg/L

Section 13 - Disposal Considerations

US EPA Waste Number & Descriptions

General Product Information

This product is not expected to be a hazardous waste when it is disposed of according to the U.S. Environmental Protection Agency (EPA) under Resource Conservation and Recovery Act (RCRA) regulations. Product characterization after use is recommended to ensure proper disposal under federal and/or state requirements.

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

Section 14 - Transport Information

International Transport Regulations

These products are not classified as dangerous goods according to international transport regulations.

Section 15 - Regulatory Information

US Federal Regulations

A: General Product Information

SARA 311/312: This product is not classified as hazardous under SARA 311/312.

B: Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

Antimony trioxide (may be in facing or adhesive) (1309-64-4)

CERCLA: 1000 lb final RQ; 454 kg final RQ

Formaldehyde (50-00-0)

SARA 302: 500 lb TPQ

CERCLA: 100 lb final RQ; 45.4 kg final RQ

State Regulations

A: General Product Information

The glass fibers in this product are not known to be regulated.
 Other state regulations may apply. Check individual state requirements.

B: Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS #	CA	FL	MA	MN	NJ	PA
Carbon black (encapsulated)	1333-86-4	Yes	No	Yes	Yes	Yes	Yes
Antimony trioxide (may be in facing or adhesive)	1309-64-4	Yes	No	Yes	Yes	Yes	Yes
Formaldehyde	50-00-0	Yes	No	Yes	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):
WARNING! This product contains a chemical known to the state of California to cause cancer.

Component	CAS #
Fiber glass wool	Not Available
Antimony trioxide (may be in facing or adhesive)	1309-64-4
Formaldehyde	50-00-0

TSCA Status

This product and its components are listed on the TSCA 8(b) inventory.

None of the components listed in this product are listed on the TSCA Export Notification 12(b) list.

International Regulations**A: General Product Information**

These products are considered articles under both U.S. and international product regulations and as such, these products do not require registration or notification on the various country-specific inventories.

B: Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Fiber glass wool	Not Available	1 % (related to Fibrous glass)

WHMIS Classification

Controlled Product Classification: D2A

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations. This SDS contains all the information required by the Controlled Products Regulations.

Section 16 - Other Information**Other Information**

Prepared for:
Johns Manville
Insulation Systems
P. O. Box 5108
Denver, CO USA 80217-5108

Prepared by:
Johns Manville Technical Center
P.O. Box 625005
Littleton, CO USA 80162-5005

The information herein is presented in good faith and believed to be accurate as of the effective date given. However, no warranty, expressed or implied, is given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

Date	MSDS #	Reason
08/01/00	1010-1.0000	New MSDS authoring system.
01/08/01	1010-1.0100	16-rev-01
03/09/01	1010-1.0101	Add EasyFit™ trade name
8/13/01	1010-1.0102	Sect. 2: Component/Information on Ingredients, added acrylic thermoset resin.
12/21/01	1010-2.0000	Update Sections 3, 11, & 15 for IARC 2001 re-classification of fiber glass wool to Group 3.
03/12/02	1010-2.0001	Sect. 1 Added trade names.
11/18/02	1010-2.0002	Sect. 1 added 5 trade names. Changed RID to BID.
02/12/03	1010-2.0003	Sect. 1: deleted 14 product names no longer sold with UPF binder (now sold only with acrylic binder; see MSDS 1021).
01/08/04	1010-2.0004	Sect. 1. Changed RID to BID.

03/23/05	1010-2.0005	Sect. 1, trade name removals: Basement Wall Insulation, Microlite L, Mobinsul, Multi-Purpose Insulation, Pan-Insul, PEBS Blanket, Rich-R Gold, Rich-R Blowing Wool, Sill Sealer, Spin Glass & UMBI. Insul-SHIELD changed to Insul-SHIELD, Faced Boards. Insul-SHIELD Black (Coated) was moved to MSDS 1009.
03/10/08	1010-2.0006	Removed the following trade names: Commercial Building Insulation; Fiber Glass Building Insulation; ITP Concrete Wall Insulation®; Laminated Metal Building Insulation; Residential Building Insulation. Updated SDS to GHS format.
09/07/2011	1010-2.0007	Regulatory update
09/08/2011	1010-2.0008	Correction sect. 8 respiratory

End of Sheet 1010