



STORAGE OF THERMAX™ (ci) EXTERIOR INSULATION

The following are recommendations when storing THERMAX™ (ci) Exterior Insulation:

- Do not leave THERMAX™ (ci) Exterior Insulation products exposed to direct sunlight for longer than 180 days.
- Store above standing water.
- Keep product tarpred or covered to protect from weather.
- If possible store product indoors.
- If product does get wet, allow it to air dry before covering with exterior coverings.
- Foam boards are light weight and loose boards can be blown around by wind. Weigh down loose boards until they are securely attached to the structure.
- For both indoor and outdoor storage adhere to all local building and fire codes. (References include NFPA 230 - Standard for the Fire Protection of Storage, NFPA 13 – Installation of Sprinkler Systems and the applicable ICC International Code or Local Building Code)

www.thermaxwallssystem.com

Technical Information
1-866-583-BLUE (2583)
Sales Information
1-800-232-2436

IN THE U.S.
THE DOW CHEMICAL COMPANY
200 Larkin
Midland, MI 48674

NOTICE: No freedom from any patent owned by Dow or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. Dow assumes no obligation or liability for the information in this document. NO EXPRESS WARRANTIES ARE GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY DOW. ALL IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

THERMAX™ products should be used only in strict accordance with product application instructions. THERMAX™ products, when used in a building containing combustible materials, may contribute to the spread of fire. For more information, consult MSDS and/or call Dow at 1-866-583-BLUE (2583). In an emergency, call 1-989-636-4400.

WARNING: Rigid foam insulation does not constitute a working walkable surface or qualify as a fall protection product.

Building and/or construction practices unrelated to building materials could greatly affect moisture and the potential for mold formation. No material supplier including Dow can give assurance that mold will not develop in any specific system.

