

DESCRIPTION

FS-K7751 is a pressure sensitive tape with a Foil-Scrim-Kraft lamination. Coated with a high performance, flame retardant cold weather acrylic adhesive. FS-K7751 has excellent adhesion capability at normal application temperatures combined with a superior low temperature performance. The epoxy resin coating contributes good surface anti-corrosion against moisture. Designed for tear resistant sealing, the release liner provides easy removal for efficient on-site application. Classified UL 723 and mold resistant.

APPLICATIONS

- Seaming and joining joints of Foil-Scrim-Kraft (FSK) laminated board and jacketing insulation.

TECHNICAL DATA

Total Thickness	6.8 mils
Backing Thickness	4.8 mils
Tensile	27.3 lb/in.
Adhesive	Acrylic
Adhesion	60 oz/in.
Operating Temperature	-31°F ~ 248°F / -35°~ 120°C
Application Temperature	-4°F to 104°F (-20°C to 48°C)
Elongation	1.0
Fire Rating	UL 723

Call for samples or additional information.

1.800.461.8273 / www.echotape.com / info@echotape.com

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.