



High Tensile Kraft Flatback Tape

FB-K4329

DESCRIPTION

FB-K4329 is a 7.5 mils Kraft flatback pressure sensitive, paper tape. Its tough carrier remains strong under moist conditions and has been specifically engineered for containerboard applications. Developed with ease-of-use and durability in mind, FB-K4329 has been tailored with an easy release while exceeding performance requirements for core-starting and tabbing applications. Good cross-direction tensile makes it suitable as a splicing tape

APPLICATIONS

- Linerboard
- Corrugating medium (fluting)
- Kraftliner
- Testliner
- Core-starting
- Tabbing

FEATURES

- Excellent tensile strength
- Excellent adhesive bond to most packaging products and surfaces
- Good moisture resistance
- Hand and machine dispensable

TECHNICAL DATA

Thickness	7.5 mils
Carrier	Natural Kraft paper
Tensile Strength	50 lbs./in.
Adhesive	Rubber
Adhesion	50 oz./in.
Elongation	2.5%

Call for samples or additional information.

1.800.461.8273 / www.echotape.com / info@echotape.com

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.