

## DESCRIPTION

FS-G7731 is a 3-way reinforced polypropylene film/scrim/Kraft facing tape, combined with a high performance cold weather solvent acrylic adhesive. Features an easy release silicone treated liner. A superior quick stick at normal operating temperatures and great performance at low temperatures.

## APPLICATIONS

- Vapor seal / seaming on Lamtec® WMP®-VR faced insulation  
Lamtec and WMP are registered trademarks of Lamtec Corporation.

## FEATURES

- High performance adhesive
- Good adhesion to polypropylene
- Excellent vapour barrier & low WVTR

## TECHNICAL DATA

Total Thickness	8.5 mils
Backing Thickness	7.8 mils
Tensile	42 lbs/in
Adhesive	Acrylic
Adhesion	40.0 oz/in
Application temperature	-4°F to 104°F (-20°C to 48°C)
Service temperature	-40°F to 176°F (-40°C to 80°C)
Elongation	1.0 %

Call for samples or additional information.

1.800.461.8273 / [www.echotape.com](http://www.echotape.com) / [info@echotape.com](mailto:info@echotape.com)

The information cited is in good faith and has been established from sources held to be secure and reliable. The values listed are typical properties. Individual rolls may vary slightly from these values. All ECHOtape products are warranted to be free of defects at time of shipment. Many factors can affect the use and performance of a product in a particular application and the user must, by test or otherwise, determine suitability for purpose; Edelstein makes no representation or warranty, express or implied, concerning any application and usage of its products. If ECHOtape product is proved defective, the exclusive remedy, shall be for Edelstein to replace the defective product. ECHOtape shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental or consequential, regardless of the legal theory asserted, including but not limited to, contract, negligence, warranty or strict liability.