HIGH-DENSITY BLOWING WOOL B-773

Your home has been professionally insulated to provide

OMEOWNER'S	NAME:					
ADDRESS:						
CITY:			STATE:	ZIP:		
		RECORD OF II	NSTALLATION			
	BLOWING WO	OOL		BATTS AND ROLLS		
■ New Construction	If F	Retrofit:		R-Value Thickness	Area Insulated	
■ Retrofit	De	pth of Previous Insulatior	n (in.) Ceili	ingi	n sq. ft.	
Number of Bags Used			us Insulation	_		
Area Insulated (sq. ft.)			on in Attic Wal			
Thickness of Insulation					n sq. ft.	
R-Value of Insulation			Floo			
n-value of insulation			1100			
D VALUE	High-Densit	y Blowing Wool B-	773, Bag Weight 31 BAGS PER		n sq. ft.	
R-VALUE	MINIMUM INSTALLED THICKNESS	SETTLED THICKNESS	BAGS PER 1,000 SQ. FT.	lb. Nominal MAXIMUM NET COVERAGE	MINIMUM WEIGHT PER SQ. FT.	
R-VALUE To obtain an insulation resistance	MINIMUM INSTALLED	SETTLED THICKNESS Expected thickness	BAGS PER 1,000 SQ. FT. Minimum number of	lb. Nominal	MINIMUM WEIGHT	
To obtain an	MINIMUM INSTALLED THICKNESS Installed insulation	SETTLED THICKNESS	BAGS PER 1,000 SQ. FT.	Ib. Nominal MAXIMUM NET COVERAGE Contents of this bag	MINIMUM WEIGHT PER SQ. FT. Weight per sq. ft. of installed insulation	
To obtain an insulation resistance (R) of:	MINIMUM INSTALLED THICKNESS Installed insulation not to be less than: 5.2 in.	SETTLED THICKNESS Expected thickness after long-term settling has occurred: 5.1 in.	BAGS PER 1,000 SQ. FT. Minimum number of bags per 1,000 sq. ft. of net area: 11.3	Ib. Nominal MAXIMUM NET COVERAGE Contents of this bag should not cover more than: 89 sq. ft.	MINIMUM WEIGHT PER SQ. FT. Weight per sq. ft. of installed insulation should not be less than: 0.350 lbs.	
To obtain an insulation resistance (R) of:	MINIMUM INSTALLED THICKNESS Installed insulation not to be less than: 5.2 in. 6.1 in.	SETTLED THICKNESS Expected thickness after long-term settling has occurred: 5.1 in. 6.0 in.	BAGS PER 1,000 SQ. FT. Minimum number of bags per 1,000 sq. ft. of net area: 11.3 13.4	Ib. Nominal MAXIMUM NET COVERAGE Contents of this bag should not cover more than: 89 sq. ft. 75 sq. ft.	MINIMUM WEIGHT PER SQ. FT. Weight per sq. ft. of installed insulation should not be less than. 0.350 lbs. 0.414 lbs.	
To obtain an insulation resistance (R) of:	MINIMUM INSTALLED THICKNESS Installed insulation not to be less than: 5.2 in.	SETTLED THICKNESS Expected thickness after long-term settling has occurred: 5.1 in.	BAGS PER 1,000 SQ. FT. Minimum number of bags per 1,000 sq. ft. of net area: 11.3	MAXIMUM NET COVERAGE Contents of this bag should not cover more than: 89 sq. ft. 75 sq. ft. 51 sq. ft.	MINIMUM WEIGHT PER SQ. FT. Weight per sq. ft. of installed insulation should not be less than: 0.350 lbs.	
To obtain an insulation resistance (R) of: 11 13 19 22 26	MINIMUM INSTALLED THICKNESS Installed insulation not to be less than: 5.2 in. 6.1 in. 8.8 in. 10.0 in. 11.7 in.	SETTLED THICKNESS Expected thickness after long-term settling has occurred: 5.1 in. 6.0 in. 8.7 in. 9.9 in. 11.5 in.	BAGS PER 1,000 SQ. FT. Minimum number of bags per 1,000 sq. ft. of net area: 11.3 13.4 19.6 22.8 27.0	MAXIMUM NET COVERAGE Contents of this bag should not cover more than: 89 sq. ft. 75 sq. ft. 51 sq. ft. 44 sq. ft. 37 sq. ft.	MINIMUM WEIGHT PER SQ. FT. Weight per sq. ft. of installed insulation should not be less than: 0.350 lbs. 0.414 lbs. 0.608 lbs. 0.706 lbs. 0.838 lbs.	
To obtain an insulation resistance (R) of: 11 13 19 22 26 30	MINIMUM INSTALLED THICKNESS Installed insulation not to be less than: 5.2 in. 6.1 in. 8.8 in. 10.0 in. 11.7 in. 13.2 in.	SETTLED THICKNESS Expected thickness after long-term settling has occurred: 5.1 in. 6.0 in. 8.7 in. 9.9 in. 11.5 in. 13.1 in.	BAGS PER 1,000 SQ. FT. Minimum number of bags per 1,000 sq. ft. of net area: 11.3 13.4 19.6 22.8 27.0 31.3	MAXIMUM NET COVERAGE Contents of this bag should not cover more than: 89 sq. ft. 75 sq. ft. 51 sq. ft. 44 sq. ft. 37 sq. ft. 32 sq. ft.	MINIMUM WEIGHT PER SQ. FT. Weight per sq. ft. of installed insulation should not be less than: 0.350 lbs. 0.414 lbs. 0.608 lbs. 0.706 lbs. 0.838 lbs. 0.972 lbs.	
To obtain an insulation resistance (R) of: 11 13 19 22 26 30 38	MINIMUM INSTALLED THICKNESS Installed insulation not to be less than: 5.2 in. 6.1 in. 8.8 in. 10.0 in. 11.7 in. 13.2 in. 16.1 in.	SETTLED THICKNESS Expected thickness after long-term settling has occurred: 5.1 in. 6.0 in. 8.7 in. 9.9 in. 11.5 in. 13.1 in. 15.9 in.	BAGS PER 1,000 SQ. FT. Minimum number of bags per 1,000 sq. ft. of net area: 11.3 13.4 19.6 22.8 27.0 31.3 40.1	MAXIMUM NET COVERAGE Contents of this bag should not cover more than: 89 sq. ft. 75 sq. ft. 51 sq. ft. 44 sq. ft. 37 sq. ft. 32 sq. ft. 25 sq. ft.	MINIMUM WEIGHT PER SQ. FT. Weight per sq. ft. of installed insulation should not be less than: 0.350 lbs. 0.414 lbs. 0.608 lbs. 0.706 lbs. 0.838 lbs. 0.972 lbs. 1.244 lbs.	
To obtain an insulation resistance (R) of: 11 13 19 22 26 30	MINIMUM INSTALLED THICKNESS Installed insulation not to be less than: 5.2 in. 6.1 in. 8.8 in. 10.0 in. 11.7 in. 13.2 in.	SETTLED THICKNESS Expected thickness after long-term settling has occurred: 5.1 in. 6.0 in. 8.7 in. 9.9 in. 11.5 in. 13.1 in.	BAGS PER 1,000 SQ. FT. Minimum number of bags per 1,000 sq. ft. of net area: 11.3 13.4 19.6 22.8 27.0 31.3	MAXIMUM NET COVERAGE Contents of this bag should not cover more than: 89 sq. ft. 75 sq. ft. 51 sq. ft. 44 sq. ft. 37 sq. ft. 32 sq. ft. 25 sq. ft. 21 sq. ft.	MINIMUM WEIGHT PER SQ. FT. Weight per sq. ft. of installed insulation should not be less than: 0.350 lbs. 0.414 lbs. 0.608 lbs. 0.706 lbs. 0.838 lbs. 0.972 lbs.	
To obtain an insulation resistance (R) of: 11 13 19 22 26 30 38 44	MINIMUM INSTALLED THICKNESS Installed insulation not to be less than: 5.2 in. 6.1 in. 8.8 in. 10.0 in. 11.7 in. 13.2 in. 16.1 in. 18.1 in.	SETTLED THICKNESS Expected thickness after long-term settling has occurred: 5.1 in. 6.0 in. 8.7 in. 9.9 in. 11.5 in. 13.1 in. 15.9 in. 17.9 in.	BAGS PER 1,000 SQ. FT. Minimum number of bags per 1,000 sq. ft. of net area: 11.3 13.4 19.6 22.8 27.0 31.3 40.1 46.9	MAXIMUM NET COVERAGE Contents of this bag should not cover more than: 89 sq. ft. 75 sq. ft. 51 sq. ft. 44 sq. ft. 37 sq. ft. 32 sq. ft. 25 sq. ft.	MINIMUM WEIGHT PER SQ. FT. Weight per sq. ft. of installed insulation should not be less than: 0.350 lbs. 0.414 lbs. 0.608 lbs. 0.706 lbs. 0.838 lbs. 0.972 lbs. 1.244 lbs. 1.453 lbs.	
To obtain an insulation resistance (R) of: 11 13 19 22 26 30 38 44 49 60	### MINIMUM INSTALLED THICKNESS Installed insulation not to be less than: 5.2 in. 6.1 in. 8.8 in. 10.0 in. 11.7 in. 13.2 in. 16.1 in. 18.1 in. 19.6 in. 22.7 in.	SETTLED THICKNESS Expected thickness after long-term settling has occurred: 5.1 in. 6.0 in. 8.7 in. 9.9 in. 11.5 in. 13.1 in. 15.9 in. 17.9 in. 19.5 in.	BAGS PER 1,000 SQ. FT. Minimum number of bags per 1,000 sq. ft. of net area: 11.3 13.4 19.6 22.8 27.0 31.3 40.1 46.9 52.6	MAXIMUM NET COVERAGE Contents of this bag should not cover more than: 89 sq. ft. 75 sq. ft. 51 sq. ft. 44 sq. ft. 37 sq. ft. 25 sq. ft. 21 sq. ft. 19 sq. ft. 19 sq. ft. 15 sq. ft.	MINIMUM WEIGHT PER SQ. FT. Weight per sq. ft. of installed insulation should not be less than. 0.350 lbs. 0.414 lbs. 0.608 lbs. 0.706 lbs. 0.838 lbs. 0.972 lbs. 1.244 lbs. 1.453 lbs. 1.631 lbs.	
To obtain an insulation resistance (R) of: 11 13 19 22 26 30 38 44 49 60	### MINIMUM INSTALLED THICKNESS Installed insulation not to be less than: 5.2 in. 6.1 in. 8.8 in. 10.0 in. 11.7 in. 13.2 in. 16.1 in. 18.1 in. 19.6 in. 22.7 in.	SETTLED THICKNESS Expected thickness after long-term settling has occurred: 5.1 in. 6.0 in. 8.7 in. 9.9 in. 11.5 in. 13.1 in. 15.9 in. 17.9 in. 19.5 in.	BAGS PER 1,000 SQ. FT. Minimum number of bags per 1,000 sq. ft. of net area: 11.3 13.4 19.6 22.8 27.0 31.3 40.1 46.9 52.6	MAXIMUM NET COVERAGE Contents of this bag should not cover more than: 89 sq. ft. 75 sq. ft. 51 sq. ft. 44 sq. ft. 37 sq. ft. 32 sq. ft. 25 sq. ft. 21 sq. ft. 19 sq. ft.	MINIMUM WEIGHT PER SQ. FT. Weight per sq. ft. of installed insulation should not be less than: 0.350 lbs. 0.414 lbs. 0.608 lbs. 0.706 lbs. 0.838 lbs. 0.972 lbs. 1.244 lbs. 1.453 lbs. 1.631 lbs.	
To obtain an insulation resistance (R) of: 11 13 19 22 26 30 38 44 49 60	### MINIMUM INSTALLED THICKNESS Installed insulation not to be less than: 5.2 in. 6.1 in. 8.8 in. 10.0 in. 11.7 in. 13.2 in. 16.1 in. 18.1 in. 19.6 in. 22.7 in.	SETTLED THICKNESS Expected thickness after long-term settling has occurred: 5.1 in. 6.0 in. 8.7 in. 9.9 in. 11.5 in. 13.1 in. 15.9 in. 17.9 in. 19.5 in.	BAGS PER 1,000 SQ. FT. Minimum number of bags per 1,000 sq. ft. of net area: 11.3 13.4 19.6 22.8 27.0 31.3 40.1 46.9 52.6	MAXIMUM NET COVERAGE Contents of this bag should not cover more than: 89 sq. ft. 75 sq. ft. 51 sq. ft. 44 sq. ft. 37 sq. ft. 25 sq. ft. 21 sq. ft. 19 sq. ft. 19 sq. ft. 15 sq. ft.	MINIMUM WEIGHT PER SQ. FT. Weight per sq. ft. of installed insulation should not be less than: 0.350 lbs. 0.414 lbs. 0.608 lbs. 0.706 lbs. 0.838 lbs. 0.972 lbs. 1.244 lbs. 1.453 lbs. 1.631 lbs.	
To obtain an insulation resistance (R) of: 11 13 19 22 26 30 38 44 49	MINIMUM INSTALLED THICKNESS Installed insulation not to be less than: 5.2 in. 6.1 in. 8.8 in. 10.0 in. 11.7 in. 13.2 in. 16.1 in. 18.1 in. 19.6 in. 22.7 in. CTOR SIGNATURE:	SETTLED THICKNESS Expected thickness after long-term settling has occurred: 5.1 in. 6.0 in. 8.7 in. 9.9 in. 11.5 in. 13.1 in. 15.9 in. 17.9 in. 19.5 in. 22.6 in.	BAGS PER 1,000 SQ. FT. Minimum number of bags per 1,000 sq. ft. of net area: 11.3 13.4 19.6 22.8 27.0 31.3 40.1 46.9 52.6	MAXIMUM NET COVERAGE Contents of this bag should not cover more than: 89 sq. ft. 75 sq. ft. 51 sq. ft. 44 sq. ft. 37 sq. ft. 25 sq. ft. 21 sq. ft. 19 sq. ft. 19 sq. ft. 15 sq. ft.	MINIMUM WEIGHT PER SQ. FT. Weight per sq. ft. of installed insulation should not be less than. 0.350 lbs. 0.414 lbs. 0.608 lbs. 0.706 lbs. 0.838 lbs. 0.972 lbs. 1.244 lbs. 1.453 lbs. 1.631 lbs.	

HIGH-DENSITY BLOWING WOOL B-773 INSULATION

Bag Weight 31 lb. Nominal

High-Density Blowing Wool B-773, Bag Weight – 31 lb. Nominal

R-VALUE	MINIMUM INSTALLED THICKNESS	SETTLED THICKNESS	BAGS PER 1,000 SQ. FT.	MAXIMUM NET COVERAGE	MINIMUM WEIGHT PER SQ. FT.
To obtain an insulation resistance (R) of:	Installed insulation not to be less than:	Expected thickness after long-term settling has occurred:	Minimum number of bags per 1,000 sq. ft. of net area:	Contents of this bag should not cover more than:	Weight per sq. ft. of installed insulation should not be less than:
11	5.2 in.	5.1 in.	11.3	89 sq. ft.	0.350 lbs.
13	6.1 in.	6.0 in.	13.4	75 sq. ft.	0.414 lbs.
19	8.8 in.	8.7 in.	19.6	51 sq. ft.	0.608 lbs.
22	10.0 in.	9.9 in.	22.8	44 sq. ft.	0.706 lbs.
26	11.7 in.	11.5 in.	27.0	37 sq. ft.	0.838 lbs.
30	13.2 in.	13.1 in.	31.3	32 sq. ft.	0.972 lbs.
38	16.1 in.	15.9 in.	40.1	25 sq. ft.	1.244 lbs.
44	18.1 in.	17.9 in.	46.9	21 sq. ft.	1.453 lbs.
49	19.6 in.	19.5 in.	52.6	19 sq. ft.	1.631 lbs.
60	22.7 in.	22.6 in.	65.6	15 sq. ft.	2.033 lbs.

Read This Before You Buy

What You Should Know About R-Values.

The chart shows the R-value of this insulation. "R" means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy.

There are other factors to consider. The amount of insulation you need depends mainly on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your fuel-use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel.

To get the marked R-value, it is essential that this insulation be installed properly with pneumatic equipment.

