



**ANY JOB.
ANY SIZE.
ANY PLACE.**

55 Years of American Ingenuity

2800-G



The **2800-G** is specifically designed for contractors to provide a smaller designed footprint with an 18 hp Briggs and Stratton V-Twin gas engine. Capable of blowing all major brands of cellulose and fiberglass to the manufacturer's specifications.

- Adaptable fold down loading door
- Removable all steel airlock allows quick access for maintenance
- User friendly 12 VDC electric dashboard
- Clear acrylic safety guard allows for easy inspection
- Durable powder coat finish
- Large hopper capacity for less reloading time
- Control panel with engine controls, pressure gauge and air bleed off
- 5 plus gallon fuel tank w/emergency shut off
- Positive Displacement Blower

MATERIAL PRODUCTION RATE

	MATERIAL
CELLULOSE	3600 (1633) *
	120 Bags per hr.*
FIBERGLASS	2100 (953) *
	70 Bags per hr.*

* lbs/hr (kg/hr) rating with 150 ft. (45.8 m.) of 3" (7.6 cm.) hose at 16 ft. (4.8 m.) elevation.

NOTE:

Manufacturer's product brand, density and variable blowing conditions will affect production rate.

Backed by a manufacturer's
2-YEAR WARRANTY - Made in the U.S.A.



KRENDL

The Innovator in Insulation Equipment™

2800-G

Scan to learn more about Krendl Machine

• **HOPPER CAPACITY** •

40 cu. ft. (1.13 m³)

Loading made easy with built in adaptable tray

• **WEIGHT/DIMENSIONS** •

1250 lbs / 39"W x 68 1/2"D x 73"H

555 kg./ 99cm x 174cm x 185cm

• **BLOWER/SIZE** •

Positive Displacement Blower

Blower System yields

135 CFM @ 6 PSI

• **AIRLOCK** •

Slideout Airlock System

16" x 12" diameter

(40.6cm. x 30.4cm. diameter)

3" (7.6cm.) Outlet

• **CONTROL PANEL** •

w/engine controls, pressure gauge and air bleed off



12 VDC Electric Dashboard

w/LED start & stop buttons



Dual Agitators

Designed for Constant Material Flow



Positive Displacement Blower

w/135 CFM @ 6 psi



18 hp Briggs & Stratton V-Twin Gas Engine

W/Positive Pressure Lubrication System