



### Self-Locking Washers (Round)

Type	K100	K120	K150	K200
Diameter	1"	1-3/16"	1-1/2"	2"
Thickness	0.015 nom.	0.015 nom.	0.015 nom.	0.015 nom.
Material	Mild Steel	Mild Steel	Mild Steel	Mild Steel
Plating	Galv.	Galv.	Galv.	Galv.
Edges / flat or beveled	Flat	Beveled	Beveled	Beveled
Other materials available	Alum., S.S.	Alum., S.S.	Alum., S.S.	Alum., S.S.
Packaged per carton	1000	1000	1000	1000

MIDWEST FASTENERS Self-Locking Washers are used in conjunction with MIDWEST FASTENERS weld pins, insul-anchors and lacing anchors to fasten insulation in place. Simply press the self-locking washer onto the pin up to the insulation until the desired position is reached. Then clip off, (or bend over) the remaining portion of pin for a permanent attachment.

Both Round or Square self-locking washers are available as a matter of design or application preference. The domed, multi-lanced hole design provides for ease of locating washer on pin and positive locking. Washers are manufactured with a beveled edge to prevent the washer from cutting into the insulation facing.

MIDWEST FASTENERS Self-Locking Washers are available according to the chart above and with standard 10 GA, 3mm, 12 GA, or 14 GA hole sizes off-the-shelf. Other material/plating combinations and hole sizes are available by special order.

**Please click the Request Information button to configure your Self-Locking Washers (Round).**