



Paintable Acrylic Caulk with Silicone

DESCRIPTION

Acrylic Caulk with Silicone is a superior quality latex caulk. Silicone is added to increase adhesion & durability, guaranteed for 40 years. Very easy to apply and tool. This Caulk provides a weather-tight flexible seal against air, dust and moisture around doors, windows, vents and more. Environmentally safe, low odor and water clean up makes this an ideal caulk for use indoors around the home.

FEATURES

- 40 year durability
- Cured caulk will resist mold and mildew growth.
- Paintable
- Easy to apply & tool
- Remains flexible
- Soap & Water clean-up
- Low odor
- Air/moisture resistant

USES

Acrylic Caulk with Silicone is ideal for sealing around doors, windows, baseboards, molding and other gaps and cracks that appear around the home. Can also be used to seal duct seams and other ventilation pipes to reduce air leaks. Adheres to most common building materials such as wood, brick, glass, concrete, aluminum, glass, plaster, drywall, ceramic and more.

LIMITATIONS

- Apply at temperatures above 40°F(5°C) but below 120°F(49°C).
- Do not apply outdoors when rain or freezing temperatures are expected within 24 hours.
- Do not use for architectural joints, joints subject to heavy abrasion or wear, or tuck-pointing.
- Do not use below water line or for aquariums or between non-porous surfaces.
- Do not use on mirrors.
- If joint size should exceed 3/8" x 3/8" use backing material.

PACKAGING

12 – 10oz cartridges per case
12 – 6oz squeeze tubes per case

COLOR OFFERING

10oz – White, Almond, Clear, Cedar, Clay,
Gray, Dark Brown, Bronze
6 oz – White

COVERAGE

1/4" round bead: Approx. 30 lin. ft./10oz cartridge
1/8" round bead: Approx. 122 lin. ft./10oz cartridge

STORAGE

- Protect from freezing. Store between 40°F(5°C) and 100°F(38°C)
- Shelf life is 12 months (unopened)

VOC-Colors <33g/l or <1%wt.
-Clear <2g/l or 1%wt.

APPLICATION PROCEDURES

Preparation

- Remove old caulk. Silicone remaining on surface will decrease adhesion.
- Clean thoroughly to remove dirt, grease, oil, wax, lose paint, dust and soap film.
- Remove mildew with bleach and detergent that does not contain ammonia. Rinse surface and allow to dry.

Directions:

- Cut tip on a slant to desired bead size.
- Insert cartridge in caulk gun.
- Apply steady pressure forcing caulk onto surface for a smooth bead.
- Smooth bead with wet finger or putty knife to desired appearance. Wipe off excess with damp cloth.
- Paintable in 30 minutes, depending on temperature and humidity.
- Allow 24 hours before exposing to water.
- Periodically clean cured caulk with non-abrasive cleanser for best appearance.

Clean-up:

Clean tools and excess caulk with soap & water before caulk dries.

CAUTION! CONTAINS Ethylene Glycol and Mineral Spirits. KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

LIMITED 40-YEAR WARRANTY

If within 40 years from the date of purchase this product, when used as directed, cracks, peels or separates, return sales receipt and used container to OSI Sealants Inc, 7405 Production Drive, Mentor, Ohio 44060 for product replacement. The seller will not accept liability for more than product replacement. THE FOREGOING WARRANTIES ARE IN LIEU OF ALL OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR ANY PURPOSE NOT EXPRESSLY SET FORTH HEREIN.

For additional information, please contact Technical Services 1-800-624-7767.

OSI[®]**OSI Sealants Inc.**

A subsidiary of Sovereign Specialty Chemicals, Inc.
Mentor, Ohio 44060

Made in USA

Phone: 800-624-7767

Fax: 440-974-8774

www.polyseamseal.com

sD20635