



This home has been professionally insulated with

Owens Corning PROPINK® L77 PINK Fiberglas™ Unbonded Loosefill Insulation

(Job Site Address)

Name _____

Address _____

City _____ State _____ Zip _____

Owens Corning™ PROPINK® L77 PINK Fiberglas™ Unbonded Loosefill Insulation

Owens Corning will accept no responsibility when the product is not installed in accordance with the product label. Stated R-value is provided by installing the required number of bags at a thickness not less than the labeled minimum thickness. Installation of the required number of bags may yield more than the specified minimum thickness. Failure by the installer to provide both the required bags and at least the minimum thickness will result in lower insulation R-value.

Specification for Open Blow Attics

New Construction Retrofit

Number of bags used

Estimated R-value of previous insulation

Area of coverage (sq. ft.)

Other type(s) of insulation in attic

Thickness of insulation

Depth of previous insulation

Attics

R-value	Bags Per 1000 Sq.Ft.	Maximum Net Coverage	Minimum Weight/ Sq. Ft.	Minimum Thickness (in)	Minimum Settled Thickness ¹
R-13	5.5	182.9	0.180	4.75	4.75
R-19	8.1	124.2	0.266	6.75	6.75
R-22	9.4	106.3	0.311	7.75	7.75
R-26	11.2	89.6	0.368	9.00	9.00
R-30	13.0	77.0	0.428	10.25	10.25
R-38	16.8	59.5	0.555	12.75	12.75
R-44	20.1	49.8	0.662	14.75	14.75
R-49	22.6	44.2	0.747	16.25	16.25
R-60	28.5	35.1	0.940	19.50	19.50

Walls

R-value	Minimum Thickness	Installed Density Lbs. Per Cu. Ft.	Maximum Coverage Per Bag	Bags Per 1000 Sq. Ft.	Minimum weight Lbs. Per Sq. Ft.
13	3.5 (2x4)	1.3	87.0	11.5	0.379
15	3.5 (2x4)	1.5	75.4	13.3	0.438
21	5.5 (2x6)	1.3	55.4	18.1	0.596
24	5.5 (2x6)	1.8	40.0	25.0	0.825

Floors

R-value	Minimum Thickness	Installed Density Lbs. Per Cu. Ft.	Maximum Coverage Per Bag	Bags Per 1000 Sq. Ft.	Minimum weight Lbs. Per Sq. Ft.
31	2x8	1.4	39.0	25.6	0.846
39	2x10	1.4	30.6	32.7	1.079
48	2x12	1.5	23.5	42.6	1.406

Cathedral Ceiling

R-value	Minimum Thickness	Installed Density Lbs. Per Cu. Ft.	Maximum Coverage Per Bag	Bags Per 1000 Sq. Ft.	Minimum weight Lbs. Per Sq. Ft.
28	2x8	1.3	42.0	23.8	0.785
36	2x10	1.3	32.9	30.4	1.002
44	2x12	1.3	27.1	36.9	1.219

¹This product shows negligible settling.

Loosefill insulations vary in thermal performance due to factors such as aging, mean temperature, settlement, convection, moisture absorption and installation variation. Convection in glass loosefill insulation installed in open attics can reduce its thermal performance in extreme winter temperatures during the heating season.

Contractor _____ Date _____ Builder _____ Date _____

Company _____ (Signature) _____ Company _____ (Signature) _____

Address _____ Address _____

Phone _____ Phone _____



OWENS CORNING INSULATING SYSTEMS, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO, USA 43659
1-800-GET-PINK®
www.owenscorning.com

Pub. No. 10012954. Printed in U.S.A. September 2010.
The color PINK is a registered trademark of Owens Corning.
©2010 Owens Corning.