



INNOVATIONS FOR LIVING™

This home has been professionally insulated with

ThermaGlas® Loosefill Insulation

(Job Site Address)

Name _____

Address _____

City _____ State _____ Zip _____

ThermaGlas Loosefill Insulation

Stated R-Value is provided by installing the required number of bags per 1,000 sq. ft. at a thickness not less than the label minimum thickness. Installation of the required number of bags may yield more than the specified minimum thickness and minimum sq. ft. weight. Failure by the installer to provide both the required number of bags and at least the minimum thickness will result in lower insulation R-Value.

Specification for Open Blow Attics		Nominal net weight of insulation is 35 lbs.				
	R-Value*	Minimum Bags per 1,000 sq. ft.	Maximum Coverage per Bag in sq. ft.	Minimum Weight in lbs./sq. ft.	Minimum Initial Installed Thickness in inches ¹	Minimum Settled Thickness in inches ¹
New Construction						
Retrofit						
Number of bags used						
Estimated R-value of previous insulation	To obtain an insulation resistance (R) of:	No. of bags per 1,000 sq. ft. of net area shall not be less than:	Contents of each bag should not cover more than:	Weight in lb. per sq. ft. of installed insulation should not be less than:	Installed insulation should not be less than:	Installed insulation should not be less than:
Area of coverage (sq. ft.)	60	37.6	26.6	1.32	23¼	23¼
Other type(s) of insulation in attic	49	30.8	32.5	1.08	19	19
Thickness of insulation	44	27.9	35.8	0.98	17¼	17¼
Depth of previous insulation	40	25.1	39.8	0.88	15½	15½
	38	23.9	41.9	0.84	14¾	14¾
	30	19.0	52.6	0.67	11¾	11¾
	26	16.2	61.8	0.57	10	10
	22	13.8	72.7	0.48	8½	8½
	19	12.1	82.4	0.43	7½	7½
	11	6.9	145.3	0.24	4¼	4¼

¹This product shows negligible settling.

Unisol Volu-Matic II machine was used to determine the coverage information above. The machine was set up in 4th gear, with a 75% open gate and 3" hose, blowing wool out in a 10' arc.

Do not store this product outside as the bag is not weather proof and is not UV protected from direct sun light.

Loosefill insulations vary in thermal performance due to factors such as aging, mean temperature, settlement, convection, moisture absorption and installation variation.

Convection in glass loosefill insulation installed in open attics can reduce its thermal performance in extreme winter temperatures during the heating season.

*The higher the R-value, the greater the insulating power. Ask your seller for the fact sheet on R-values.

Blanket Insulation

Blanket and batt fiber glass insulation, when installed according to the manufacturer's recommendations, will provide the stated R-Value.

R-VALUE	R-38	R-38C	R-30	R-30C	R-25	R-22	R-21	R-19	R-15	R-13	R-11
To obtain an insulation resistance (R) of:											
MINIMUM THICKNESS											
Installed insulation should be:	12"	10.25"	9.5"	8.25"	8.0"	6.75"	5.5"	6.25" [†]	3.5"	3.5"	3.5"
THE FOLLOWING PRODUCTS HAVE BEEN INSTALLED AS SPECIFIED ABOVE:											
	kraft	unfaced	foil	FS-25	R-Value	Thickness	No. Pkgs.	Coverage Area			
Ceilings	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	_____	_____	_____	_____			
Floors	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	_____	_____	_____	_____			
Walls	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	_____	_____	_____	_____			
Basement	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	_____	_____	_____	_____			
Crawlspace	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	_____	_____	_____	_____			

Contractor _____ Date _____ Builder _____ Date _____

Company _____ (Signature) _____ Company _____ (Signature) _____

Address _____ Address _____

Phone _____ Phone _____



INNOVATIONS FOR LIVING™

OWENS CORNING INSULATING SYSTEMS, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO 43659
1-800-GET-PINK™
www.owenscorning.com