



PROPINK® L77 PINK® Fiberglas™ Unbonded Loosefill Insulation

Manufacturers Fact Sheet

This fact sheet contains important details about Owens Corning's™ **PROPINK® L77 PINK® Fiberglas™ Unbonded Loosefill Insulation**. Read it carefully.

Owens Corning will accept no responsibility when the product is not installed in accordance with the product label. Stated R-value is provided by installing the required number of bags at a thickness not less than the label minimum thickness. Installation of the required number of bags may yield more than the specified minimum thickness. Failure by the installer to provide both the required bags and at least the minimum thickness will result in lower insulation R-value.

Open Cavity Application (Attics) Nominal Bag Weight 33 lb.

R-value	Bags Per 1,000 Sq. Ft.	Maximum Net Coverage	Minimum Weight/Sq. Ft.	Minimum Thickness (in)	Minimum Settled Thickness ¹
R-13	5.5	182.9	0.180	4.75	4.75
R-19	8.1	124.2	0.266	6.75	6.75
R-22	9.4	106.3	0.311	7.75	7.75
R-26	11.2	89.6	0.368	9.00	9.00
R-30	13.0	77.0	0.428	10.25	10.25
R-38	16.8	59.5	0.555	12.75	12.75
R-44	20.1	49.8	0.662	14.75	14.75
R-49	22.6	44.2	0.747	16.25	16.25
R-60	28.5	35.1	0.940	19.50	19.50

Closed Cavity Application (Walls)

R-value	Minimum Thickness	Installed Density Lbs. Per Cu. Ft.	Maximum Coverage Per Bag	Bags Per 1,000 Sq. Ft.	Minimum weight Lbs. Per Sq. Ft.
13	3.5 (2x4)	1.3	87.0	11.5	0.379
15	3.5 (2x4)	1.5	75.4	13.3	0.438
21	5.5 (2x6)	1.3	55.4	18.1	0.596
24	5.5 (2x6)	1.8	40.0	25.0	0.825

Closed Cavity Application (Floors and Cathedral Ceilings)

R-value	Minimum Thickness	Installed Density Lbs. Per Cu. Ft.	Maximum Coverage Per Bag	Bags Per 1,000 Sq. Ft.	Minimum weight Lbs. Per Sq. Ft.
31	7.25 (2x8)	1.4	39.0	25.6	0.846
39	9.25 (2x10)	1.4	30.6	32.7	1.079
48	11.25 (2x12)	1.5	23.5	42.6	1.406

¹ This product shows negligible settling, with no impact on thermal performance. Unisol Volu-Matic III machine was used to determine the coverage information above. The machine was set up in 3rd gear, with a 75% open gate and a 3" hose, blowing the wool out in a 10 ft. arc.

Read This Before You Buy

What you should know about R-Values:

The chart shows the R-values of this insulation. "R" means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy.

There are other factors to consider. The amount of insulation you need depends mainly on the climate you live in. Also, your fuel savings from insulation will depend on the climate, the type and size of house, the amount of insulation already in your house, and your fuel-use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel.

To get the marked R-value, it is essential that this insulation be installed properly.

Please contact 419-248-6557 for additional information. Email: gettech@owenscorning.com

Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein.



INNOVATIONS FOR LIVING™

OWENS CORNING INSULATING SYSTEMS, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO, USA 43659

1-800-GET-PINK®
www.owenscorning.com

Pub. No. 22676-I. Printed in U.S.A. December 2012. THE PINK PANTHER™ & ©1964–2012 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. ©2012 Owens Corning. All Rights Reserved.

