			This h	nome has	s been	professic	onally in	sulated v	vith				
OWENS CORNING ®				0	wen	s Co	rning	g					
OVATIONS FOR LIVING®		Batts	and	Blar	nket	Fibe	r Gla	ass In	isula	tion			
					-	Site Addres	-						
City								Si	tate		Zip		
lure by the installe Blanket and bat †R-18 in a 5.5'' c	tt fiber glass		0								de the s	tated R-Va	alue.
To obtain an in	sulation resi	R-VALUE stance (R) of:	R-38	R-38C	R-30	R-30C	R-25	R-22	R-21	R-19	R-15	R-13	R-11
		HICKNESS on should be:	12''	10.25''	9.5''	8.25''	8.0''	6.75''	5.5"	6.25''†	3.5''	3.5"	3.5''
	THE F	OLLOWIN	G PRO	DUCTS	HAVE	BEEN	INSTA	LLED A	S SPEC		ABOVI	≣:	
	Kraft	Unfaced	Foil	FS	-25	R-Valu	Je	Thickn	ess	No. p	kgs.	Covera	ge Area
Ceilings				0									
				٦]								
Floors				С									
	_	-											
Walls				C									
				C									
Basement				C C									

Contractor	Date	Builder	Date
Company(S	ignature)	Company	(Signature)
Address		Address	
Phone		Phone	

OWENS CORNING ®

Crawlspace

OWENS CORNING INSULATING SYSTEMS, LLC ONE OWENS CORNING PARKWAY TOLEDO, OHIO, USA 43659

1-800-GET-PINK[®] www.owenscorning.com Pub. No. 10012236. Printed in U.S.A. January 2010. The color PINK is a registered trademark of Owens Corning. ©2010 Owens Corning.