

Product Data Sheet



- R-10, 3.4"
- R-11, 3.7"
- R-13, 4.3"
- R-16, 5.3"
- R-19, 6.3"
- R-25, 8.0"
- R-30, 9.25"

Description

Owens Corning Certified R Metal Building Insulation is a light density fibrous glass blanket designed to be laminated with a variety of appropriate facings. Certified R is available in standard R-values of 10, 11, 13, 16, 19, 25 and 30. Standard roll widths are 36", 48", 60" and 72". Selected Made-to-Order widths are also available. The product complies with the North American Insulation Manufacturers Association (NAIMA) Standard 202-96 (Rev. 2000) "Standard for Flexible Fiber Glass Insulation Used in Metal Buildings".

PureFiber[®] Technology Advances

- Made with natural¹ materials, formaldehyde-free² and soft to the touch
- Uses a minimum of 50% recycled content—30% being post-consumer

Physical Property Data

Property	Test Method	Result
Moisture Absorption	ASTM C 1104	<2% by weight
Fungi Resistance	ASTM C 1338	provides no sustenance
Fire Hazard Classification	UL 723 ¹ ASTM E 84, CAN/ULC S-102	FHC 25/50
Noncombustibility	ASTM E 136	Noncombustible

¹The surface burning characteristics of these products have been determined in accordance with UL 723. This standard should be used to measure and describe the properties of materials, products or assemblies in response to heat and flame under controlled laboratory conditions and should not be used to describe or appraise the fire hazard or fire risk of materials, products or assemblies under actual fire conditions. However, results of this test may be used as elements of a fire risk assessment which takes into account all of the factors which are pertinent to an assessment of the fire hazard of a particular end use. Values are reported to the nearest 5 rating.

- GREENGUARD Children and Schools CertifiedSM and GREENGUARD Indoor Air Quality Certified[®]
- Thickness recovery provides outstanding thermal and acoustical performance

Uses

Certified R Metal Building Insulation is used as part of the insulation system in the roofs and side walls of metal buildings. It is designed to be laminated with a variety of facings to provide attractive interior finishes, abuse resistance, and assistance in control of moisture.

Application

Several methods are used to insulate metal buildings. The usual method is to apply the insulation over the structural members (purlins and girts) and inside the exterior panels. This method generally accommodates single layer installations. Methods are also available to apply insulation between purlins so as to accommodate greater insulation thicknesses and better thermal performance.

Availability

Owens Corning Certified R Metal Building Insulations are fabricated and distributed by a nation wide network of independent laminators assuring prompt service and delivery. Contact your Owens Corning Sales Representative for the names of insulation laminators servicing your area.

Certified Thermal Performance

Owens Corning Certified R Metal Building Insulation is regularly tested to ensure compliance to the NAIMA 202-96 (Rev. 2000) Standard. Sampling and testing is performed by the National Association of Home Builders Research Laboratories (NAHBR). The product is labeled on the top surface of each roll with the nominal R-value and the "NAIMA 202-96" (Rev. 2000) to indicate compliance. The NAIMA 202-96 (Rev. 2000) standard specifies thermal performance which provides the capability of obtaining nominal thermal resistance (R-values) after laminating. The actual thermal performance obtained from the laminated product will depend

Product Data Sheet

primarily on the recovered thickness. Note that these nominal R-values are for the insulation only and do not include the effects of facings, air films, compression of insulation at framing members, conductance through fasteners, or other heat transfer paths particular to an installation.

The recovered thickness achieved will depend on a number of variables determined in the laminating process and hence are outside of Owens Corning's control. To address these issues, a number of leading metal building insulation laminators produce products which meet the National Insulation Association's "Certified Faced Insulation Standard" (NIA 404). Samples of faced products are periodically tested by a nationally recognized laboratory and determined to meet the NIA standard.

Specification Compliance

- NAIMA 202-96 (Rev. 2000)
Standard for Flexible Fiber Glass Insulation Used in Metal Buildings
- ASTM C 991-03 Type I, Flexible Glass Fiber Insulation for Metal Buildings

Notes

1. Unfaced insulation made with a minimum of 99% by weight natural materials consisting of minerals and plant-based compounds (not including packaging).
2. Applies to the insulation component only.

Disclaimer of Liability

Technical information contained herein is furnished without charge or obligation and is given and accepted at recipient's sole risk. Because conditions of use may vary and are beyond our control, Owens Corning makes no representation about, and is not responsible or liable for the accuracy or reliability of data associated with particular uses of any product described herein. Nothing contained in this bulletin shall be considered a recommendation.

Scientific Certification Systems (SCS) provides independent verification of recycled content in building materials and verifies recycled content claims made by manufacturers. For more information, visit www.scs-certified.com.

The GREENGUARD INDOOR AIR QUALITY CERTIFIED Mark is a registered certification mark used under license through the GREENGUARD Environmental Institute.



INNOVATIONS FOR LIVING[®]

OWENS CORNING INSULATING SYSTEMS, LLC
ONE OWENS CORNING PARKWAY
TOLEDO, OHIO 43659
1-800-GET-PINK[®]
www.owenscorning.com

Pub. No. 15086-Q. Printed in U.S.A. June 2011. THE PINK PANTHER[™] & ©1964-2011 Metro-Goldwyn-Mayer Studios Inc. All Rights Reserved. The color PINK is a registered trademark of Owens Corning. ©2011 Owens Corning.

