

PULLDOWN LADDER JACKET (THE ANSWER TO ATTIC ACCESS ENERGY CODES)

BENEFITS OF PULLDOWN LADDER JACKET:

- Increases energy savings
- Non-toxic
- Excellent vapor barrier
- Installs easily with Crown stapler
- Superior thermal performance
- Flexible and durable
- Improves insulation system performance
- Great for new construction or retrofits
- Reflects up to 97% of radiant heat
- Simple installation and heavy duty zipper allows for easy attic access.
- Insert insulation batt into pocket and close the Velcro tab
- Staple tabs to attic opening framing and caulk or foam for air sealing.
- **Insulation insertion and Installation video clips are on the website**



OVERALL R-VALUE for COMPLETE ASSEMBLY

ADD BATT	OVERALL R-VALUE
R-13	R-22.1
R-19	R-28.1
R-30	R-39.1
R-38	R-47.1

MODEL #	DESCRIPTION	SIZE
LEF2355	Ladder Jacket -Med	22.5" x 54"x10"
LEF2555	Ladder Jacket -Large	25" x 54" x 10"
LEF3060	Ladder Jacket XL *	29.5 x 59" x10"

ASTM C518 Testing provided by:

R & D Services
P.O.Box 2400 Cookeville, TN
38502-2400



- XL Jacket also ideal for 4 foot knee wall access doors.
- Full size knee wall attic access door sizes are available

FOAM INSULATION PRODUCT SHEET

ESP LOW-E® Insulation

PRODUCT CODES: 4LFLT, 4LFLS, 4LFLZ, 5LFLT, 6LFLT, 6LFLS, 6LFLZ

PRODUCT DIMENSIONS & DESCRIPTIONS: Double sided scrimmed aluminum foil laminated to polyethylene foam (1/4" nominal thickness)

CORE MATERIAL: Polyethylene

FACINGS AVAILABLE: Foil/Foil

FLAME AND SMOKE: ASTM E-84

FLAME SPREAD: Less than 25, SMOKE DEVELOPED: Less than 50

FULL SCALE FIRE TEST: NFPA 286 - Foil/Foil Passed

R-VALUE: Up to R-9 without added insulation*

PERM RATING: E-96 - .008

WARNING: Although Insulation Products are all fire tested to ASTM and/or NFPA standards; it is recommended that they or any insulation material should not be exposed to open flame or other ignition sources of sufficient intensity during shipment, storage or installation.



Appalachian Insulation Supply, Inc.

Toll Free Phone: (877) 944-7697

Toll Free Fax: (800) 251-1498

www.ais1.us