

Insulation Retaining Clip

- + Mechanically secures RainBarrier® continuous insulation (ci) to exterior substrate
- + Packaged in cartons of 250
- + Available for overnight delivery and can also be top loaded on truckloads of Thermafiber products and LTL shipments
- + Quick and easy to install
- + Compatible with various wall tie systems and hangers



Thermafiber®
THE NAME IN MINERAL WOOL™



Made in the USA



Thermafiber® RainBarrier® Clip



Thermafiber RainBarrier Clips are compatible with multiple types of masonry ties. RainBarrier continuous insulation (ci) was installed on the University of Michigan North Quad project in Ann Arbor, MI.

Front

Back



Thermafiber RainBarrier Clip is used in typical wire or shelf-type wall tie applications.

Thermafiber® RainBarrier® Clip

Description:

Thermafiber RainBarrier Clip mechanically secures RainBarrier continuous insulation (ci) to the exterior substrate of the building and is compatible with multiple types of masonry and façade tie systems. These clips are quick and easy to install on any jobsite and can be shipped overnight to the jobsite or in conjunction with Thermafiber material.

Product Options:

- Thermafiber RainBarrier Clips are available in cartons of 250

Installation:



Insulation is friction fitted between the wall ties as shown.



After installing the insulation, secure with a RainBarrier clip utilizing the center notches to secure directly on the wire tie as shown. Repeat process with the next horizontal row of RainBarrier insulation.



If using a flange or flat style hanger, installation of insulation is friction fit between ties forming a seam (a typical size is 16" on center). After installing the insulation, secure with RainBarrier clip as shown.

For more information, please refer to the Thermafiber RainBarrier Installation Guide on our website: www.thermafiber.com/rainbarrier

Thermafiber Insolutions®:

Thermafiber offers industry leading technical and engineering assistance to architects, specifiers, and contractors. These services include CAD drawings, engineering judgments, LEED Credit Information, and product recommendations. Contact our technical services department at 1-888-834-2371 x-295, or email technicalservices@thermafiber.com.

For Further Information:

For additional information about these or other Thermafiber products contact us at 1-888-834-2371 or visit our website www.thermafiber.com.

Notice:

THERMAFIBER, Inc. shall not be liable for incidental and consequential damages, directly or indirectly sustained, nor for any loss caused by application of these goods not in accordance with current printed instructions or for other than the intended use. THERMAFIBER liability is expressly limited to replacement of defective goods. Any claim shall be deemed waived unless made in writing within thirty (30) days from date it was or reasonably should have been discovered.

Submittal Approvals:

Job Name	
Contractor	Date

