



PRODUCT ANNOUNCEMENT

Touch 'n Seal® 1.75 PCF FR ICC

Two Component Low-Pressure Spray Polyurethane Foam (SPF) System

ICC Evaluation Services has issued **ESR-3052** for Touch 'n Seal 1.75 pcf FR SPF system.

Touch 'n Seal 1.75 pcf FR ICC has been evaluated for use as thermal insulation in Type V (B) construction.



Features:

- ASTM E-84 Class A (I) fire resistance at 2 inch foam thickness
- Air-impermeable at 1 inch foam thickness
- Class II vapor barrier at 2 inch foam thickness
- Approved for use in attics and crawlspaces under specified conditions with an approved alternative ignition barrier coating
- IFT DC-315 is approved as an alternative thermal barrier coating per NFPA 286
- Extended 15 month shelf life

Available ICC Products:

4004001200	Foam Kit 200 FR ICC
4004521600	Foam Kit 600 FR ICC Complete
4004521601	Foam Kit 600 FR ICC Replacement
4505500750	CP-750 FR ICC (CPDS)
4505200000	RF-17 FR ICC (Refillable)
4505170000	RF-60 FR ICC (Refillable)
4505113000	RF-120 FR ICC (Refillable)



Hose and Applicator Assemblies for Disposable 200/600 ICC Foam Kits:

4004590327	15 ft YELLOW Applicator with Standard Accessory Pack
4004590337	30 ft YELLOW Applicator with Standard Accessory Pack



Convenience Products
 866 Horan Dr., Fenton, MO 63026 USA • 1-800-325-6180
 www.touch-n-seal.com
 Country of Origin: USA



52093-030314-TNS